

STOCK COLOR PROGRAM

THE SBC ADVANTAGES

Highest Quality Standards Ever

- Minimum 3-7/16" shingles width:
 15% larger than industry standard.
- · Graded on both faces.
- R&R precision 1/64" to 10": Truest R&R shingles on the market.
- Kiln-dried by dehumidification:
 Producing shingles that are less brittle and susceptible to cracking.
- Exclusive factory finished "dipping" process: Putting more stain where it counts, below the 5" exposure line.
- Easy installation system:
 - Nail line on every shingle
 - Installation tool
 - Touch-up kits









WHITE CEDAR GRADES



Extra RR « A »



Top Grade, no imperfections.

Sidewall Select RR « AB »



No imperfections on exposed face (up to 6"), wider shingles Clear RR « B »



No imperfections on exposed face (up to 6") 2nd Clear Regular and RR « C »



Sound knots on exposed face

Calculating the Quantity Required Area Covered by 1 box

Exposures	Area Covered							
4"	20 sq. ft.							
4.5"	22.5 sq. ft.							
5" (standard)	25 sq. ft.							

IN STOCK PROGRAM

pDc			Extra « A		ktra RR « A »		Sidewall Select RR « AB »		Clear RR « B »		R 	2 nd Clear Regular and RR « C »		gular C »	Warranty	
PPU			Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Finish	Wood Decay
Solid Color	Buzzards Bay Gray	>/		Х	Х					х	X				1 coat = 10 years, including 2 years labor 2 coats = 25 years including 5 years labor	30 years, including 5 years labor
	Cape Cod Gray	///		x	X					x	×					
	Concord White	//						×								
	Driftwood Gray	///					X	Х								
	Green Tea Leaf	///					X	x								
	Harbor Gray	//					X	X								
	Montauk Sand	//					Х	×								
	Monterey Gray	//		Х	X					X	X					
	Nantucket Gray	///					X	x								
	Safari Beige	//					X	x								
	Sandstone	//		X	X					х	×					
	Sea Shell	>/					Х	X								
Naturaltone	Olympic Maximum 57503	>/					X								NO	30 years, including 5 years labor
	Enviro Bleach	>/		Х						X					NO	30 years, including 5 years labor
Weathering Agents	Bleaching Oil	//					X									
	Weathering Stain	//					X									
Primer (Must be top-coated within 6 months)	Pro-prime	11					×								NO	30 years, including 5 years labor
Natural -	Green		X			Х			X			X			Ne.	NO
	Kiln-Dried (KD)		X			Х			X			X			NO	