

THE SBC ADVANTAGES



TRUEST R&R SHINGLES ON THE MARKET

R&R precision 1/64" up to 10" from the butt



REVERSIBLE SHINGLES

Graded on both sides



DURABLE FINISH

Exclusive factory-finished dipping process putting more stain below the 5" exposure line



15% WIDER THAN **INDUSTRY STANDARD**

A minimum width of 3-7/16



OPTIMAL WOOD STABILITY

Kiln-dried by dehumidification producing less brittle shingles



VALUABLE TIME-SAVER FEATURES

Embossed nailing line on every shingle, installation tool and touch-up kits





UP TO 3X FASTER!





WHITE CEDAR GRADES



Extra « A »



- Superior quality
- No imperfections

Sidewall Select « AB »



- Wider for faster installation
- · No imperfections on exposed surface

Clear « B »



- · Standard quality
- · No imperfections on exposed surface

2nd Clear « C »



- Economy quality Sound knots, rustic appearance

Calculating the Quantity Required Area Covered by 1 box

•									
Exposures	Area Covered								
4"	20 sq. ft.								
4.5"	22.5 sq. ft.								
5" (standard)	25 sq. ft.								

IN-STOCK PROGRAM

$\mathbf{p}\mathbf{D}\mathbf{c}$			Extra «A»		Sidewall Select « AB »		Clear « B »			2 nd Clear «C»			Warranty			
Jan 1			Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Finish	Wood Decay
Solid colors	Buzzards Bay Gray	>/					Х	Х							1 coat = 10 years, including 2 years labor 2 coats = 25 years including 5 years labor	30 years, including 5 years labor
	Cape Cod Gray	//		X	Х		Х	Х		х	Х					
	Concord White	//						х								
	Driftwood Gray	//					Х	X								
	Green Tea Leaf	///					Х	X								
	Harbor Gray	//					Х	Х								
	Montauk Sand	//					Х	х								
	Monterey Gray	//					Х	Х								
	Nantucket Gray	///					Х	X								
	Safari Beige	//					Х	X								
	Sandstone	//					x	×								
	Sea Shell	>/					X	х								
Naturaltone	Olympic Maximum 57503	>/					х								NO	30 years, including 5 years labor
Weathering Agents	Enviro Bleach	/		X			Х			X					NO	30 years, including 5 years labor
	Bleaching Oil	>/					Х									
	Weathering Stain	>/					Х									
Primer (Must be top-coated within 6 months)	Gray Pro-prime	//					Х								- NO	30 years, including 5 years labor
	White Pro-prime	71					Х									
Natural	Green		Х			Х			×			×			NO	NO
	Kiln-Dried (KD)		Х			Х			X			Х				